



Jiffy-tite™ Self-Sealing, Quick-Connect Fluid Fittings

These lightweight Jiffy-tite™ Quick-Connect fittings are designed specifically for motor racing. They provide superior seal integrity under extreme racing conditions. Made of high-quality aircraft aluminum with brass valves and stainless steel ball bearings, they are corrosion resistant for extra long life. **Fittings are available in 2000, 3000 and 5000 Series based upon the required rate of fluid flow. (See chart for results of flow tests.) Check out these features:**

- Standard fluorocarbon seals are resistant to gasoline, oil, water and coolant
- Available with Buna seals for alcohol & methanol or EPDM seals for nitromethane or hydraulic fluid
- Patented design – designed specifically for racing
- Lightweight – lighter than competitor's fittings
- Good-looking black & gold anodized finish
- Durable 6061-T6 aluminum bodies, brass valves and stainless steel ball bearings
- Connects by hand in seconds – ribbed collar for slip proof use
- Wide variety of interchangeable adapters
- Double shut-off valves provide increased safety
- 350°F (177°C) maximum operating temperature (with standard fluorocarbon seals)
- Compact yet with high-flow capacity
- 200 psi maximum operating pressure (not for use in brake or clutch systems)
- Excellent corrosion resistance
- Excellent wear resistance
- 100% leak tested
- Rebuildable
- 360° swivel
- Made in the U.S.A.

See our website for many more Jiffy-tite™ parts!



Series	A dia. inches	B dia. inches	C dia. inches	D inches	E inches	F inches	Flow ** (valved)	Flow ** (non-valved)
2000	0.24	0.37	0.75	1.68 max	1.86 max	3.13 max	1.75 gpm	3.81 gpm
3000	0.37	0.53	1.03	2.01 max	2.34 max	3.74 max	4.34 gpm	na
5000	0.59	0.78	1.37	2.69 max	3.06 max	5.25 max	7.86 gpm	na

** Flow rates are measured using Stoddard solvent at 80° F with a 5 psi inlet pressure through a mated pair of fittings attached to the following hose lengths:
2000 series: 3 ft of -6 hose; 3000 series: 2 ft of -8 hose; 5000 series: 2 ft of -10 hose

PLUMBING

Fitting Type

	2000 Series Jiffy-tite™ Fittings		3000 Series Jiffy-tite™ Fittings		5000 Series Jiffy-tite™ Fittings	
	2000 Socket	2000 Plug	3000 Socket	3000 Plug	5000 Socket	5000 Plug
	Part No.	Price	Part No.	Price	Part No.	Price
-4 (7/16-20) Male O-Ring Boss			JT22104	\$19.99		
-6 (9/16-18) Male O-Ring Boss			JT22106	\$20.99	JT32106	\$23.69
-8 (3/4-16) Male O-Ring Boss					JT32108	\$24.79
-10 (7/8-14) Male O-Ring Boss						JT52110 \$48.99
3AN Female	JT21303 \$33.29	JT22303 \$20.49				
4AN Female	JT21304 \$34.99	JT22304 \$22.39				
6AN Female	JT21306 \$36.89	JT22306 \$23.59	JT31306 \$42.39	JT32306 \$27.49		
8AN Female			JT31308 \$44.59	JT32308 \$28.39	JT51308 \$66.99	JT52308 \$48.49
10AN Female					JT51310 \$70.29	JT52310 \$52.19
12AN Female					JT51312 \$73.79	JT52312 \$58.49
3AN Male	JT21403 \$28.89	JT22403 \$18.49				
4AN Male	JT21404 \$30.49	JT22404 \$19.49				
6AN Male	JT21406 \$31.99	JT22406 \$20.39	JT31406 \$36.89	JT32406 \$23.49	JT51408 \$62.59	JT52408 \$45.29
8AN Male			JT31408 \$38.79	JT32408 \$24.59	JT51410 \$65.59	JT52410 \$48.69
10AN Male					JT51412 \$68.99	JT52412 \$51.59
12AN Male						
-4 Hose Barb (0.22")	JT21504 \$30.59	JT22504 \$18.29				
1/4" Pushlock Hose Barb	JT21504P \$22.99					
-6 Hose Barb (0.34")	JT21506 \$33.59	JT22506 \$20.49	JT31506 \$40.49	JT32506 \$26.49		
3/8" Pushlock Hose Barb	JT21506P \$19.99	JT22506P \$13.99	JT31506P \$30.39	JT32506P \$19.99		
-8 Hose Barb (0.44")			JT31508 \$42.33	JT32508 \$27.79	JT51508 \$66.29	JT52508 \$58.49
1/2" Pushlock Hose Barb			JT31508P \$24.99	JT32508P \$16.99		
-10 Hose Barb (0.56")					JT51510 \$91.99	JT52510 \$61.59
5/8" Pushlock Hose Barb					JT51510P \$68.99	JT52510P \$46.29
-4 Straight Hose End	JT21604 \$37.59	JT22604 \$24.89				
-6 Straight Hose End	JT21606 \$39.49	JT22606 \$26.29	JT31606 \$45.29	JT32606 \$33.59		
-8 Straight Hose End			JT31608 \$47.59	JT32608 \$35.19		
-10 Straight Hose End					JT51610 \$72.19	JT52610 \$60.19
-12 Straight Hose End					JT51612 \$75.99	JT52612 \$63.39
-6 90° Hose End	JT21606E \$45.19	JT22606E \$31.89	JT31606E \$51.69	JT32606E \$33.59		
-8 90° Hose End			JT31608E \$53.99	JT32608E \$41.59		
-10 90° Hose End					JT51610E \$79.59	JT52610E \$67.59
-12 90° Hose End					JT51612E \$83.39	JT52612E \$70.79
1/8 NPT Male	JT21802 \$33.29	JT22802 \$21.29				
1/4 NPT Male	JT21804 \$35.29	JT22804 \$22.39	JT31804 \$39.39	JT32804 \$26.19	JT51806 \$60.79	JT52806 \$47.19
3/8 NPT Male			JT31806 \$41.29	JT32806 \$28.99	JT51808 \$67.59	JT52808 \$50.59
1/2 NPT Male						

Jiffy-tite™ Part Number Builder • Use this table to construct the Jiffy-tite™ part number you need

We have many more combinations in stock than we can possibly list here; please see our website or give us a call. If we don't have it, we can order it for you!

Digit 1	Digit 2	Digit 3	Digits 4 & 5	Letter (optional)	
2 = 2000 Series 3 = 3000 Series 5 = 5000 Series	1 = Socket 2 = Plug	1 = O-Ring Boss Adapter 3 = Female AN Adapter 4 = Male AN Adapter 5 = Hose Barb Adapter*	6 = Reusable Hose End 7 = Female NPT Threads 8 = Male NPT Threads	AN Dash Size or NPT Size	A = Non-Valved B = Buna N (Nitrile) Seals C = Non-Valved, Buna N Seals D = 45° Elbow E = 90° Elbow
				BD = 45° Elbow, Buna N Seals BE = 90° Elbow, Buna N Seals F = EPDM Seals M = Lanyard P = Pushlock Hose Barb*	

* Hose barb fits AN-type hose (such as our Nitrile-Lined Hose on page 86). Pushlock hose barb fits rubber hose (such as our Textile-Reinforced Hose on page 88).